Dingli Scissor Lifts Product Manuals













Self-propelled Rough-Terrain Scissor Lifts(Electric&Engine Large-scale Type)

Model:JCPT3214DC - JCPT2812DC - JCPT2223DC/RTB - JCPT2212DC - JCPT1912DC - JCPT1823DC/RT JCPT1523DC/RT - JCPT1418DC/RT - JCPT1218DC/RT

The large-scale rough-terrain scissor lifts series can be divided into two categories: electric driving and engine driving. The maximum working height covers 12-32m and the maximum load is 750kg. With advantages of great height, heavy load, large platform and strong power, it can be qualified for more severe working conditions and meet various indoor and outdoor work requirements.

In addition to all the advantages of engine drive types, in view of the pure electric design, the electric drive rough-terrain scissor lift series also takes into account the environmental advantages of noiseless, zero emission and so on. It is suitable for the operation environment with high environmental requirements, such as SGCC, nuclear power plant, SINOPEC, CNPC, residential area, airport, tunnel, etc.



One-key Extended Platform (Apply to JCPT2223)



4WD&4WS(Apply to JCPT3214/JCPT2814
JCPT2223/JCPT2212)



Strong Gradeability



Automatic Leveling Outriggers

Model = Electric = Engine	JCPT1523RT
Size	
Max. Working Height	15.00m
Max. Platform Height	13.00m
Overall Height(Rails Up)	2.98m
Overall Height(Rails Down)	2.28m
Overall Length(With Outriggers)	4.88m
Overall Length(Without Outriggers)	3.98m
Overall Width	2.27m
Platform Size(Length×Width)	3.98×1.83m
Platform Extension Size(Front/Back)	1.43m/1.16m
Ground Clearance(Stowed/Raised)	0.30m
Wheelbase	2.86m
Turning Radius(Inside/Outside)	2.35m/5.20m
Tyres	33×12-20
Performance	
Max. Occupants	7
Gradeability	50%
Up/Down Speed	70/52sec
S.W.L	680kg
S.W.L On Extension	227kg
Travel Speed(Stowed)	6.1km/h
Travel Speed(Raised)	1.1km/h
Max. Working Slope	2°/3°
Weight	
Overall Weight(With Outriggers)	8420kg
Overall Weight(Without Outriggers)	7900kg
Power	
Battery	1
Charger	1
Driving Motor	1
Lifting Motor	1
Diesel Engine Kubota D1105	36.5kW/2600rpm
Diesel Tank	100L
Hydraulic Tank	130L
Other Configurations	
4×4 Driving Self-leveling Hydraulic Outriggers	s Slide-out Engine Tray Dual Extended Platform