

# LSW3


EN\_CTS\_LSW3\_22-02\_r2.0

The lighting power of 4x320W LED floodlights and a very narrow canopy design makes LSW3 the most compact and eco-friendly lighting tower ever created! This mobile lighting tower will help you to skimp up to 75% of fuel and protect our environment with a reduction in carbon emissions up to 10 Ton per year, compared to a traditional lighting tower with metal halide lamps.



## LED LAMPS

High efficiency LED floodlights.



## MCP - MANUAL CONTROL PANEL

The MCP\* includes fuel level gauge, engine alarms, starting key, on/off switches for lamps and magneto-thermal cutout switch with differential relay. A digital control panel is available upon request.

\*Data and photo are for illustrative purpose only. Features may change without prior notice.

### LSW3

TECHNICAL DATA				
Min. dimensions (mm)	Length x Width x Height	2480 x 1190 x 2450		
Max. dimensions (mm)	Length x Width x Height	2480 x 2400 x 8000		
Dry weight (kg)		658		
Engine models available*		Yanmar L70N**	Yanmar 2TNV70	Kubota Z482
Avg. sound pressure	dB(A) @ 7m	63	61	60
Total running time (h)		200	171	171
Lifting system	M:Manual / H:Hydraulic	M		
Mast rotation (°)		340		
Wind speed resistance (km/h)		80		
Lamps power (W)		4 x 320		
Lamps type		LED		
Total lumen (Lm)		188160		
Illuminated area (m <sup>2</sup> )		4500		
Alternator	kVA/V/Hz	5/220/50 - 5/240/60		
Outlet socket	kVA/V/Hz	2/220/50 - 2/240/60		
Tank capacity (liters)		120		
Liquid containment tank (110%)	√:Yes / ●:No	√		

\*\* Not globally available. Please check with local dealer or subsidiary before ordering.